



**POSEIDON, LLC dba POSEIDON BARGE**

725 East Parr Road, Berne, IN 46711

PH: 866-99-BARGE; FAX: 260-589-2088

WEBSITE: [www.poseidonbarge.com](http://www.poseidonbarge.com)



**AEMA**  
Association of  
Equipment Manufacturers

# POSEIDON® FABRICATION SOLUTIONS

*CUSTOMER CONCEPT TO REALITY*  
*FABRICATION, BENDING, CUTTING, WELDING*

## MODERN MANUFACTURING FACILITY

- Over 130,000 Square feet of manufacturing space
- Assembly areas are equipped with 30, 25, 20, 15, 10, 6 and 5 ton cranes
- Indoor loading bay for semi loading

## CUSTOM FABRICATION

- Customers can work with Poseidon® Engineering to create manufacturing drawings used for fabrication
- Customer supplied DXF files are also accepted

## PLASMA TABLE

- Bolt Hole Precision Software for clean, accurate holes
- Auto-nest software to insure max efficiency / affordability
- 2.0" Plate maximum cutting thickness
- 16 gauge minimum cutting thickness
- Maximum plate size 13' x 44'
- Customer provides DXF files
- 10 ton overhead crane
- Stocking 1/4" to 1" A36 plate, additional plate thicknesses available locally

## NEW HIGH DEFINITION MESSER PLASMA TABLE

- Messer Titan III Cutting System
- Maximum Sheet Width – 12'
- Maximum Sheet length – 44'
- Cutting Thickness:
  - o Minimum Thickness – 10 GA.
  - o Maximum Thickness – 1.50"
- Hypertherm Software: ProNest
- True Hole Nesting Software
- Auto Nesting

## SAW

- Part cut lengths up to 48' lengths
- Maximum cut size 16" round bar or 16" high x 18" wide at 90°
- Maximum cut size 13" round bar or 16" high x 11" wide at 45°
- Maximum cut load 5,000 lbs.

## **NEW HYDMECH MODEL H-28A-120 AUTOMATIC BANDSAW**

- Round Maximum Cut – 28”
- Rectangular Maximum Cut – 28”x28”
- Maximum 6 Cant – 24” x 28”
- Maximum Workload – 30,000lbs.
- Maximum Cut Length – 50’

## **IRON WORKER**

- 110 Ton metal working capacity
- Shearing up to: 24” x 5/8” or 16” x 3/4”
- Notching: max thickness 1/2”, max depth 3-1/2”, max width 2”
- Punch - 1-1/2” diameter x 3/4” thick maximum

## **MIG WELDING CAPABILITIES**

- AWS D 1.1 Standards
- AWS Certified Welders are available for specific project needs
- Flux Core & Hard Wire Metals
- 90% Argon-10% CO2 shielding gas standard

## **FABRICATION ASSEMBLY**

- Eight 45’ x 13’ production tables to fabricate custom work

## **NEW COMBI-LIFT**

- 10,000 lb Workload Capacity
- Moves structural steel faster, rotating wheels
- A continual improvement effort saving on handling time

## **STOCKING / STORAGE**

- Stocking of customer blanket purchases
- Release per customer schedule
- Indoor storage

## **BRAKE PRESS**

- 440 Tons Maximum Capacity, 12’ wide x 18” deep
- CNC controller positions the back gage & adjusts MI max thickness at a 90° bend
- 16 GA A36 Min thickness
- 1/2” & 3/4” 90° bends

**CALL TODAY!**



**AEM**  
Association of  
Equipment Manufacturers

**Contact: Scott Sprunger  
PH: 866-992-2743**

**E-mail: [ssprunger@poseidonbarge.com](mailto:ssprunger@poseidonbarge.com)**