

POSEIDON® P2-7 PORTABLE SECTIONAL BARGES



	P2-7-20 Section		P2-7-40 Section	
Length, Overall	20'-4"	6.20 m	40'-4"	12.29 m
Width, Overall	10'-4"	3.15 m	10'-4"	3.15 m
Height, Overall	7'-0"	2.13 m	7'-0"	2.13 m
Shipping Weight, Approx.	17,000 lbs	7,711 kg	31,400 lbs	14,243 kg
Draft, Unloaded	17"	0.43 m	16"	0.41 m
Draft, Full Load	42"	1.07 m	42"	1.07 m
Payload at Full Load	13.0 tons	11.8 mT	27.4 tons	24.9 mT



Standard Features:

- Baril DCC Paint System including Zinc Rich Primer Coat & High Performance Topcoat
- Flush Mounted, Sacrificial Zinc Anodes provide added Corrosion Protection
- Internal Void Spaces Coated with Biofloat Environmentally Friendly Corrosion Inhibitor
- Grade 50 Deck Plate with raised lug tread pattern for increased traction, providing 5000 PSF distributed load capacity and 25,000 PSF concentrated load capacity

Available Poseidon Accessories:

- Spud Pockets
- Spuds, 24" diameter x 1/2" wall thickness, in a wide range of lengths from 20ft to 80ft
- Double Drum Hydraulic Winch Systems
- Pocket Mounted Winch Systems
- Deck Cleats, Handrail, Safety Ladder
- Sea Bee Thruster System



Poseidon® P2-7 40ft and 20ft Barge sections are built using drawings approved by the American Bureau of Shipping, in accordance with the ABS Rules for Building and Classing Steel Vessels for Service on Rivers and Intercoastal Waterways.



POSEIDON® BARGE, LTD

725 East Parr Road, Berne, IN 46711

PH: 866-99-BARGE; FAX: 260-589-2088

WEBSITE: www.poseidonbarge.com

STOCK LOCATIONS: Berne, IN • Plain, WI • Mt Airy, NC • Houston, TX
Cocoa, FL • Coeymans, NY • St. Louis, MO • Morgan City, LA • Rio City, CA